

Pneumatic **MK** Dispenser TS478LX

2-K 400 ml 10:1 SBS Cartridge



Suitability <ul style="list-style-type: none"> • Force 2.7 kN (~270 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 400 ml • Material Viscosity Medium • Professional Use 	[mm]	10:1	
	a	184,0	
	b	69,0	
	c	92,0	
	d	25,0	

Part Number	Article	Description	Packaging
DP2 400-27-100	151787	Weight 1.86 kg, Length 497 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Quick reloading	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
fax +1 603 893 37 37
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com